


CEMENT CONCRETE DRIVEWAY 6" THICK

MATCH EXISTING DRIVEWAY GRADE

1/2" WIDE FULL DEPTH EXPANSION JOINT



CURB TRANSITION

DETAIL

2" LIP UNLESS APPROVED BY DIRECTOR OR DESIGNEE


*WING DIMENSIONS MAY REQUIRE MODIFICATION TO MEET ADA STANDARDS.

NOTE:

1. MATERIAL - WSDOT CONCRETE CLASS 4000psi.
2. SEE CHAPTER 3, ENGINEERING DEVELOPMENT GUIDE.
3. FULL DEPTH EXPANSION JOINT SHALL BE INSTALLED IF DRIVEWAY WIDTH IS 10' OR GREATER.
4. CURB SHALL BE IN COMPLIANCE WITH STND DWG 312.
5. MODIFICATION TO THIS DESIGN SHALL BE APPROVED BY THE DIRECTOR OR DESIGNEE THROUGH A VARIANCE REQUEST.
6. NO REBAR SHALL BE PLACED IN CURB, GUTTER, DRIVEWAY, OR SIDEWALK.



Public Works
Planning and
Development
Services



Driveway Approach: Reverse Slope without Amenity Zone

304

NOT TO SCALE

Revision Date
December 2006